NISSAN NV200 COMBI EURO 5
TECHNICAL SPECIFICATIONS

NV200 COMBI GRADES

The NV200 Combi offers supreme versatility for the carriage of both cargo and passengers, as well as the superb load carrying capacity of the van. Equipped with either 5 or 7 seats it can carry a full complement of passengers, or the fully folding rear seats make way for a large cargo area. With a compact exterior, but large interior space, combined with a tight turning circle NV200 is easy to manoeurve and park.

Please note that NV200 Combi is a passenger car for registration and taxation purposes (including benifits in kind)

S GRADE

SAFETY AND SECURITY
- ABS + EBD
- Driver airbag + Passenger airbag
- Immobiliser
- Remote central locking
- Superlocking
- Shielded door locks

COMFORT AND CONVENIENCE
- CD/FM audio with 4 speakers
- MP3 aux jack
- Bluetooth
- Electric mirrors
- Front electric windows
- Steering rake adjustment
- 13 Cabin storage areas
- Fold flat passenger seat back
- Under-seat storage
- Trip computer

COMBI CARGO AREA
- Twin rear loading doors glazed with wash wiper
- Twin sliding side doors, glazed with fixed window
- Folding 2nd row 60:40 split bench seat

STYLING
- Black bumpers & mirrors
- Full wheel cover

OPTIONS
- Metallic paint
- Rear Tailgate door

SE GRADE
FEATURES ADDITIONAL TO S GRADE

COMBI CARGO AREA
- Luggage floor protector*
- 2 sliding hooks*
- Twin sliding side doors, privacy glass

STYLING
- Alloy wheels
- Body colour bumpers

COMFORT AND CONVENIENCE
- Air conditioning
- Front fog lamps
- Rear View Camera
- Heated door mirrors

OPTIONS
- Metallic paint
- Rear Tailgate door
- 7 seat Combi version

* Not applicable with 7 seat version

SE + GRADE
FEATURES ADDITIONAL TO SE GRADE

SAFETY AND SECURITY
- ESP
- Side airbags

COMFORT AND CONVENIENCE
- Nissan Connect - Satelite Navigation
- Cruise Control
- Driver adjustable speed limiter

OPTIONS
- Metallic paint
- Rear Tailgate door
- 7 seat Combi version

NV200 COMBI

Engine		K9K 1.5 dCi			
Grade		S / SE / SE+	SE / SE+		
Seats		5	7	5	7
ENGINE					
No. of Cylinders		4			
Valves per Cylinder		2			
Engine Capacity	cm3	1461			
Bore x Stroke	mm	76.0 x 80.5			
Maximum Engine Power	hp	89 (66kw)		110 (81kW)	
	rpm	4000		4000	
Maximum Torque	Nm	200		240	
	rpm	1750		1750	
Compression Ratio		18.8		15.2	
Fuel Type		diesel			
Fuel Supply		commonrail direct injection			
Battery 12v	Ah	62		60	
Alternator	Amps	110/150*		150	
* With air conditioning, not for S grade					
DRIVE TRAIN					
Clutch type		Dry plate, mechanical			
Gearbox	Type	5 Speed Manual		6 Speed Manual	
No. Speeds		5		6	
Gearbox performances	1st*	3.727		3.727	
	2nd*	2.048		1.947	
	3rd*	1.321		1.323	
	4th*	0.971		0.975	
	5th*	0.738		0.763	
	6th*	-		0.638	
	Rev	3.545		3.687	
Final drive ratio		3.867		3.733	
Driven Wheels		Front			
*Speed (Km/h) per 1000rpm					
CHASSIS					
Suspension	Front	Strut			
	Rear	Leaf rigid			
Steering		Electric Power assisted rack & pinion			
Braking System (option)		Disc front, drum rear, ABS, EBD and brake assist			
Wheel Size		14×5.5J			
Tyre Size		175/70R14C Offset 45 P.C.D 114.3×4H			
PERFORMANCE					
Maximum Speed	Mph	98		99	
Min. Turning Circle (Wall to Wall)	m	11.1			
Min. Turning Circle (Kerb to Kerb)	m	10.6			

Engine			K9K 1.5 dCi			
Grade			S / SE / SE+	SE / SE+		
Seats			5	7	5	7
WEIGHTS						
Gross Vehicle Weight		Kg	2000		2030	
Kerb Weight	Min	Kg	1338	1378	1357	1401
Maximum Payload		Kg	662	622	673	629
Gross Axle Weight	Front	Kg	951	960	936	945
	Rear	Kg	1049	1040	1094	1085
Max. Trailer Cap.	Braked	Kg	1100			
	Unbraked	Kg	640			
OVERALL DIMENSIONS						
Length		mm	4400			
Width with mirrors		mm	2011			
Width w/o mirrors		mm	1695			
Height (Unladen)		mm	1860			
Wheelbase		mm	2725			
Overhang	Front	mm	835			
	Rear	mm	840			
Track	Front	mm	1490			
	Rear	mm	1510			
Ground Clearance (unladen)		mm	158			
LUGGAGE / CARGO AREA DIMENSIONS						
Maximum Length		mm	2040			
Maximum Width		mm	1500			
Maximum Height		mm	1358			
Minimum Width between the Wheelarches		mm	1220			
Load Platform Height (Unladen)		mm	524			
Cargo Volume (Max Cube)		m^3	2.3	0.9	2.3	0.9
- with 3rd row seat folded		m^3	-	2.1	-	2.1
- with 2nd row seat folded - 5 seats/7 seats		m^3	3.1	2.9	3.1	2.9
Side Door	Width	mm	693			
	Height	mm	1171			
Back Door	Width	mm	1262			
	Height	mm	1228			
FUEL TANK						
Fuel tank capacity		l.	55			
FUEL CONSUMPTION & EMISSIONS						
Fuel Consumption	Urban Cycle	l/100 Km / MPG	5.8 / 48.70		6.3 / 44.84	
	Extra-Urban	l/100 Km / MPG	4.9 / 57.65		5.0 / 56.50	
	Combined	l/100 Km / MPG	5.3 / 53.30		5.5 / 51.36	
CO2 mass emissions (Combined)		g/Km.	138		144	

*According to Directive 80/1268/CEE CEE; Last ammendment 2004/3/CE

SHIFT_ is an English word from a Japanese car company that best embraces our values and the mission of this corporation. No matter where you are in the world, SHIFT_ is the way we express who we are, how we work and what we are trying to accomplish.
Everything we touch, we SHIFT_. And everything we SHIFT_ we try to make better and uniquely Nissan.

Visit our websites at:
www.nissan.co.uk
www.nissan-lcv.co.uk

Dealer stamp:

NISSAN

SHIFT_the way you move

Every effort has been made to ensure that the content of this publication is correct at the time of going to press (September 2011). Vehicle shown with accessory wheel covers. In accordance with the company's policy of continuously improving its products, Nissan Europe reserves the right to change at any time the specification and the vehicles described and shown in this publication. Nissan dealers will be informed of any such modifications as quickly as possible. Please check with your local Nissan dealer to receive the most up-to-date information. All rights reserved. Reproduction in whole or part of this brochure without the written permission of Nissan Europe is forbidden.

Part Number 99999-53133. Printed in the UK.